



TRANSPORTATION EMERGENCY NO.:
(800) 424-9300 CHEMTREC
INFORMATION TELEPHONE NO.: (901) 526-2211
www.farrellcalhoun.com



MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 2200 Line
PRODUCT NAME: 100% Acrylic Exterior Satin Latex House Paint
HMIS CODES: H-1, F-0, R-0, P-B

This Material Safety Data Sheet covers Farrell-Calhoun products numbered:
2200 White, 2250 White Base, 2251 Medium Base, 2252 Deep Base, 2257 Neutral Base

==== SECTION I - MANUFACTURER IDENTIFICATION ====

MANUFACTURER'S NAME: FARRELL-CALHOUN, INC.
ADDRESS: 221 E. CAROLINA AVENUE, MEMPHIS TN 38126
TRANSPORTATION EMERGENCY NO.: (800) 424-9300 CHEMTREC
INFORMATION TELEPHONE NO.: (901) 526-2211
LAST REVISION: 10/31/07

==== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ====

REPORTABLE COMPONENTS	CAS NUMBER	Vapor Pressure mm Hg @ TEMP	PERCENT
*Tetrachloroisophthalonitrile OSHA TWA 15 mg/M ³ ACGIH TWA 15 mg/M ³	001897-45-6		1

* INDICATES TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.
May cause allergic skin reactions. May be harmful or fatal if swallowed. Causes severe eye and skin damage.
Tetrachloroisophthalonitrile is considered a possible human carcinogen (IARC: Group 2B) human evidence shows NO adequate data;
Animal evidence is sufficient.

==== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ====

APPEARANCE AND ODOR: Mild odor

EMERGENCY OVERVIEW: **CAUTION!** Skin and eye irritant. Corrosive to eyes and skin. Do Not take internally. Skin sensitizer.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Not applicable. In some individuals with prior sensitivity, allergic reactions can occur.

PRIMARY ROUTES OF ENTRY:

INHALATION: Inhalation of vapor or mist can cause headache, nausea, and irritation of nose, throat, and lungs. May be harmful or fatal if large quantities are inhaled. Severe irritation to the nose, throat, lungs and mucous membranes.

SKIN: This material may cause severe skin irritation.

EYE: This material may cause severe eye irritation including corrosive burns to the eye resulting in permanent damage.

INGESTION: Small ingested amounts are not believed to produce adverse health effects. Larger amounts (more than one ounce) should be removed from the stomach by induced vomiting or aspiration. No adverse effects anticipated. Call a physician.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE (SHORT TERM): Eyes: Severe irritant. Can cause eye burns. Corrosive. **Skin:** Little absorption is possible, but burns and allergic reactions may occur. A skin sensitizer. **Ingestion:** May cause severe irritation to the nose, throat and stomach leading to gastrointestinal irritation, vomiting, and diarrhea. Harmful or fatal if swallowed. **CHRONIC (LONG TERM):** Contains a possible carcinogen. See Section II.

==== SECTION IV - FIRST AID MEASURES ====

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Move to fresh air. If difficulty breathing, call a physician.

SKIN: Wash affected area with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

EYES: Flush eyes gently with water for at least 15 minutes, while holding eyelids apart; Seek medical attention IMMEDIATELY.

INGESTION: If swallowed, DO NOT induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact physician immediately. Amounts that enter mouth should be rinsed out until taste is gone.

==== SECTION V - FIRE FIGHTING MEASURES ====

FLASH POINT: Noncombustible

METHOD USED: n/a

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA: Use foam, CO₂, or dry chemical.

SPECIAL FIREFIGHTING PROCEDURES: When this product burns, water, carbon dioxide, carbon monoxide, and smoke are produced. Pyrolysis products may include such materials as acetic acid, acrolein, and acetaldehyde. Recommend respirator to remove smoke and organic vapor.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material can splatter above 212° degrees F. Dried product can burn.

==== SECTION VI - ACCIDENTAL RELEASE ====

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED: Dike around spill and absorb liquids with absorbent. Stop spill from entering drains, sewers, streams, or waterways. Area could be slippery. Wear resistant clothing.

==== SECTION VII - HANDLING AND STORAGE ====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store above 120 degrees F, near heat, or open flame. Do not smoke in area! Protect from freezing. **KEEP AWAY FROM CHILDREN.** Close container and keep upright to prevent leakage.

OTHER PRECAUTIONS: Do not take internally. Avoid skin and eye contact. Prevent repeated or prolonged breathing of vapor or spray mist. Follow label precautions. **KEEP AWAY FROM CHILDREN!** Use NIOSH- approved dust filter respirators when sanding to keep the TLV below the applicable limits.

===== SECTION VIII – EXPOSURE CONTROLS AND PERSONAL PROTECTION =====

RESPIRATORY PROTECTION: If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, use (MSHA/NIOSH-approved or equivalent) chemical/mechanical filters designed to remove a combination of particulates and organic vapor in open and restricted ventilation areas. Use approved airline type respirators or hoods in confined areas. Spray dusts and mists should be controlled to below 2mg/M³ through usage of NIOSH-approved dust filter respirators.
VENTILATION: Sufficient ventilation in pattern and volume in accordance with OSHA reg. 29CFR part 1910.94 should provide air contaminant concentration below applicable exposure limits. Heavy vapors should be removed from all lower work areas.
PROTECTIVE GLOVES: Gloves should be worn if skin contact is likely. Use neoprene or rubber gloves to prevent skin contact.
EYE PROTECTION: Use safety eyewear including side shields, face shields, or chemical splash goggles (ANSI Z-87.1, or approved equivalent).
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Use protective cream if skin contact is likely. Use full face shield, apron, or appropriate equipment. Availability of eye wash stations and showers recommended.
WORK/HYGIENIC PRACTICES: Wash hands before eating, smoking, or using wash room. Do not consume food or beverages where this product is handled.

==== SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES ====

BOILING RANGE: > 212F	SPECIFIC GRAVITY: 1.26
VAPOR DENSITY: Heavier than air.	EVAPORATION RATE: Slower than ether
COATING V.O.C.: 0.43 lb/gal	MATERIAL V.O.C.: 0.17 lb/gal
SOLUBILITY IN WATER: Partially miscible	

==== SECTION X – STABILITY AND REACTIVITY ====

STABILITY: Stable.
CONDITIONS TO AVOID: Products are stable in most environments. Coagulation may occur following freezing, thawing, or boiling.
INCOMPATIBILITY: Products will react violently with any water sensitive materials such as sulfuric acid or alkali such as sodium hydrates.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition may yield acrylic monomers.
HAZARDOUS POLYMERIZATION: Will not occur.

==== SECTION XI – TOXICOLOGICAL INFORMATION ====

CARCINOGENICITY: NTP CARCINOGEN:NO IARC MONOGRAPHS:YES OSHA REGULATED:YES
*SEE SECTION II NOTATION

==== SECTION XII – ECOLOGICAL INFORMATION ====

No data available.

==== SECTION XIII- DISPOSAL INFORMATION ====

WASTE DISPOSAL METHOD: The coating and any contaminated diking material should be thoroughly air-dried and collected into drums. The drums should be sealed and properly labeled with the proper waste designation and land filled or incinerated according to current local, state, and federal regulations.

==== SECTION XIV – TRANSPORT INFORMATION ====

DOT: Latex Paint (Not DOT Regulated)

==== SECTION XV – REGULATORY INFORMATION ====

WORKPLACE CLASSIFICATION

This product is considered hazardous by OSHA.

SARA TITLE III: SECTION 311/312 CATEGORIZATIONS (40CFR370)

Acute Chronic

SARA TITLE III: SECTION 313 INFORMATION (40CFR372)

Chlorothalonil CAS# 1897-45-6

CERCLA INFORMATION (40CFR302.4)

None Known

US TOXIC SUBSTANCES CONTROL ACT (TSCA)

The intentional ingredients, section II, of this product are listed.

==== SECTION XVI – DISCLAIMER ====

Although the information contained herein is believed to be reliable, there is no warranty of any kind, expressed or implied as to the completeness or accuracy thereof. Recipients are advised to confirm in advance of the need that the information is current, and applicable to their circumstances.