



TRANSPORTATION EMERGENCY NO.:  
(800) 424-9300 CHEMTREC  
INFORMATION TELEPHONE NO.: (901) 526-2211  
www.farrellcalhoun.com

## MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 470A  
PRODUCT NAME: Interior/Exterior Acrylic Latex Block Filler  
HMIS CODES: H-1, F-0, R-0, P-B

### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: FARRELL-CALHOUN, INC.  
ADDRESS: 221 E. CAROLINA AVENUE, MEMPHIS TN 38126  
TRANSPORTATION EMERGENCY NO.: (800) 424-9300 CHEMTREC  
INFORMATION TELEPHONE NO.: (901) 526-2211  
LAST REVISION: 11-25-08

### SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	Vapor Pressure mm Hg @ TEMP	PERCENT
Crystalline Silica OSHA PEL 0.05 mg/M <sup>3</sup> Resp. Dust ACGIH TLV 0.025 mg/M <sup>3</sup> Resp. Dust	14808-60-7		.24

NO TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

### SECTION III - HAZARDS IDENTIFICATION

APPEARANCE AND ODOR: Mild odor

**EMERGENCY OVERVIEW: WARNING!** Sanding dust contains possible carcinogen, do not breath dust while sanding or spray mist while applying paint. Possible nuisance dust. Mild skin and eye irritant. Do not take internally.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Not applicable. In some individuals with prior sensitivity, allergic reactions can occur.

#### PRIMARY ROUTES OF ENTRY:

**INHALATION:** Inhalation of vapor or mist can cause headache, nausea, and irritation of nose, throat, and lungs.

**SKIN:** This material may cause mild skin irritation.

**EYE:** This material may cause mild eye irritation.

**INGESTION:** Small ingested amounts are not believed to produce adverse health effects.

Larger amounts (more than one ounce) should be removed from the stomach by induced vomiting or aspiration. No adverse effects anticipated. Call a physician.

**HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE (SHORT TERM):** Eyes: mild irritation followed by redness and tearing. Skin: Little absorption is possible, but allergic reactions may occur. Ingestion: Gastrointestinal irritation or vomiting. **CHRONIC (LONG TERM): Inhalation:** This product contains over 0.1% crystalline silica (CAS# 1408-60-7) listed by NTP and IARC, which can cause lung damage (Silicosis) and possibly cancer. Control respiratory exposures to less than 0.1 mg/M<sup>3</sup> when sanding or grinding film.

**CANCER INFORMATION:** For complete discussion of toxicology data refer to Section XI.

### SECTION IV - FIRST AID MEASURES

#### EMERGENCY AND FIRST AID PROCEDURES:

**INHALATION:** Move to fresh air. If difficulty breathing, call a physician.

**SKIN:** Wash affected area with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

**EYES:** Flush eyes gently with water for at least 15 minutes, while holding eyelids apart; Seek medical attention.

**INGESTION:** If swallowed, immediately give 1 to 2 glasses of water and call a physician, hospital, emergency room or poison control center for way to induce vomiting.

### SECTION V - FIRE FIGHTING MEASURES

**FLASH POINT:** Noncombustible

**METHOD USED:** n/a

**FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** n/a **UPPER:** n/a

**EXTINGUISHING MEDIA:** Use foam, CO<sub>2</sub>, or dry chemical.

**SPECIAL FIRE FIGHTING PROCEDURES:** When this product burns, water, carbon dioxide, carbon monoxide, and smoke are produced. Pyrolysis products may include such materials as acetic acid, acrolein, and acetaldehyde. Recommend respirator to remove smoke and organic vapor.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Material can splatter above 212 degrees F. Dried product can burn.

### SECTION VI - ACCIDENTAL RELEASE

**STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:** Dike around spill and absorb liquids with absorbent. Stop spill from entering drains, sewers, streams, or waterways. Area could be slippery. Wear resistant clothing.

### SECTION VII - HANDLING AND STORAGE

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Do not store above 120 degrees F, near heat, or open flame. Do not smoke in area! Protect from freezing. **KEEP AWAY FROM CHILDREN.** Close container and keep upright to prevent leakage.

**OTHER PRECAUTIONS:** Do not take internally. Avoid skin and eye contact. Prevent repeated or prolonged breathing of vapor or spray mist. Follow label precautions. **KEEP AWAY FROM CHILDREN!** Use NIOSH- approved dust filter respirators when sanding to keep the TLV below the applicable limits.

### SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION

**RESPIRATORY PROTECTION:** None required if good ventilation is maintained. Wear respirator (NIOSH/MSHA approved) suitable for concentrations and types of air contaminants encountered. Use NIOSH/MSHA approved airline type respirator or hood in confined areas. When

sanding or abrading dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive. Spray dusts and mists should be controlled to below 0.1mg/M<sup>3</sup> through usage of NIOSH-approved dust filter respirators.  
**VENTILATION:** Sufficient ventilation in pattern and volume in accordance with OSHA reg. 29CFR part 1910.94 should provide air contaminant concentration below applicable exposure limits. Heavy vapors should be removed from all lower work areas.  
**PROTECTIVE GLOVES:** Gloves should be worn if skin contact is likely. Use neoprene or rubber gloves to prevent skin contact.  
**EYE PROTECTION:** Use safety eyewear including side shields, face shields, or chemical splash goggles (ANSI Z-87.1, or approved equivalent).  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Use protective cream if skin contact is likely. Use full face shield, apron, or appropriate equipment. Availability of eye wash stations and showers recommended.  
**WORK/HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using wash room. Do not consume food or beverages where this product is handled.

==== SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES ====

**BOILING RANGE:** > 212F  
**VAPOR DENSITY:** Heavier than air.  
**COATING V.O.C.:** 0.12 lb/gal  
**SOLUBILITY IN WATER:** Partially miscible  
**SPECIFIC GRAVITY:** 1.59  
**EVAPORATION RATE:** Slower than ether  
**MATERIAL V.O.C.:** 0.12 lb/gal

==== SECTION X – STABILITY AND REACTIVITY ====

**STABILITY:** Stable.  
**CONDITIONS TO AVOID:** Products are stable in most environments. Coagulation may occur following freezing, thawing, or boiling.  
**INCOMPATIBILITY:** Products will react violently with any water sensitive materials such as sulfuric acid or alkali such as sodium hydrates.  
**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** Thermal decomposition may yield acrylic monomers.  
**HAZARDOUS POLYMERIZATION:** Will not occur.

===== SECTION XI – TOXICOLOGICAL INFORMATION =====

**CARCINOGENICITY:** NTP CARCINOGEN: YES IARC MONOGRAPHS: YES OSHA REGULATED: YES  
This product contains over 0.1% crystalline silica which is listed by IARC and NTP. Long term exposure to high levels of silica dust, from sanding or abrading the dried paint film, may cause lung damage (silicosis) and possibly cancer.

==== SECTION XII – ECOLOGICAL INFORMATION ====

No data available.

==== SECTION XIII – DISPOSAL INFORMATION ====

**WASTE DISPOSAL METHOD:** The coating and any contaminated diking material should be thoroughly air-dried and collected into drums. The drums should be sealed and properly labeled with the proper waste designation and land filled or incinerated according to current local, state, and federal regulations.

==== SECTION XIV – TRANSPORT INFORMATION ====

**DOT:** Latex Paint (Not DOT Regulated)

==== SECTION XV – REGULATORY INFORMATION ====

**WORKPLACE CLASSIFICATION**

This product is considered hazardous by OSHA.

**SARA TITLE III: SECTION 311/312 CATEGORIZATIONS (40CFR370)**

Acute Chronic

**SARA TITLE III: SECTION 313 INFORMATION (40CFR372)**

None Known

**CERCLA INFORMATION (40CFR302.4)**

None Known

**US TOXIC SUBSTANCES CONTROL ACT (TSCA)**

The intentional ingredients, Section II, of this product are listed.

=== SECTION XVI – DISCLAIMER ===

Although the information contained herein is believed to be reliable, there is no warranty of any kind, expressed or implied as to the completeness or accuracy thereof. Recipients are advised to confirm in advance of the need that the information is current, and applicable to their circumstances.