



221 E. Carolina Avenue Memphis, TN 38126
(800) 424-9300 CHEMTREC
INFORMATION TELEPHONE NO.: (901) 526-2211
www.farrell-calhoun.com help@farrell-calhoun.com

PRODUCT DATA SHEET



370 LINE INTERIOR PREMIUM EGGSHELL LATEX ENAMEL

PRODUCT PROFILE

DESCRIPTION

The 370 line is a premium latex eggshell enamel designed for use on interior surfaces where a soft, pleasing appearance is desired, and a washable, scrubbable finish is required. In most instances this high solids product will cover in one coat except when there is a drastic color change because of the excellent hiding of this product. One of the best features of this product is the outstanding touch-up. The 370 line also has good flow and leveling, low odor, low VOC, and is non-splattering. This product meets MPI GPS-1-05 and MPI 44 standard.

TYPICAL USE

The 370 line is recommended for painting properly prepared interior walls and ceilings of plaster, wallboard, and masonry surfaces. This product is not recommended for hard service areas such as wood trim or metal surfaces.

PRIMERS

In most cases, the #370 line is self-priming and does not require any special primers. New wallboard or aged flat finishes may be sealed with this product or one coat of #380 Perfik-Seal prior to topcoating with #370 line. Prime water, smoke or other difficult stains with #697 100% Acrylic Stain Killer/Bonding Primer, #597 Stain Killer Primer or #598 Low Odor Stain Killer.

SURFACE PREPARATION

The surface to be painted should be dry and free of any dirt, chalk, grease, oil, rust, or other foreign contaminants. Remove grease and oil from the surface with a detergent solution, rinse thoroughly, and allow the surface to completely dry. Repair/Caulk all cracks and fill all small holes and other surface imperfections with putty or spackling compound and then sand to smooth finish followed by dusting. Old glossy enamel finishes must be sanded, dusted, and then primed with either #599 Enamel Undercoater, #699 Latex Enamel Undercoater or #697 Bonding Primer. If you have any questions about proper surface preparation, check your surface preparation guide or consult your Farrell-Calhoun representative.

COLOR

Available in white, medium, and deep tint bases that can be tinted to a variety of custom colors with universal colorants.

FINISH	Eggshell @ 60° 4 – 8, @ 85° 16 - 26
SOLIDS	52.0% by weight/36.4% by volume.
THEORETICAL APPLICATION RATE	575 square feet per gallon at 1.0 mil dry film thickness. Coverage figures do not include loss of material while mixing, porosity or irregularity of the surface to be painted, or application methods.
RECOMMENDED SPREAD RATE	Apply at 300-400 square feet per gallon to achieve a WFT of 4.6 Mils and a DFT of 1.7 Mils per coat.
VOC	49 grams per liter
DRY TIME	At 77°F and 50% relative humidity: Thirty minutes to dust, dirt and bug free, one hour to tack free, and four hours to recoat.
APPLICATION EQUIPMENT	Conventional or airless spray, synthetic brush or roller cover.
THINNING	Thinning is not recommended.
CLEAN-UP	Warm, soapy water.

SHIPPING & STORAGE

PACKAGING	5 Gallon Pails, 1 Gallon Cans and Quarts.
WEIGHT/GALLON	11.1 +/-0.1 Pounds
STORAGE TEMPERATURE	Minimum 35°F. Maximum 90°F.
SHELF LIFE	12 months at recommended storage temperature when stored in tightly sealed containers.
FLASH POINT	Water-based paint: Not applicable.

The technical data contained in this data sheet is accurate to the best of our knowledge. No warranty is expressed or implied since the method of application and its intended use is beyond our control.